



### 可靠

避免堵料，保障过程连续进行

### 经济

将浆料/废纸与水的比例维持在理想水平

### 方便


无接触式测量不产生磨损，无需维护

## 碎浆机

### 碎浆机液位测量和输送机进料流量检测

废纸包通过皮带输送机送入水力碎浆机中，然后加水进行破解。在这个过程中，高速转动的叶轮会将纤维疏解分离。碎浆机中的过程条件严苛，废纸包的掉落、浆料形成的漩涡和磨蚀性的异物都是测量的难点。物位仪表可准确输出浆料与水的比例，并防止皮带输送机上的废纸包积聚而发生堵料。

[更多细节](#)



#### VEGAMIP 61

使用微波开关测量料流高度

- 采用非接触式测量，不产生磨损
- 可靠检测料流高度
- 仪表无需清洗，测量免维护

[产品细节](#)



#### VEGABAR 82

使用静压式液位计测量碎浆机液位

- 探头与脱气器罐壁表面齐平
- 耐磨蚀能力强
- 陶瓷测量元件无磨损，可长期服役

[产品细节](#)

PRO

## VEGAMIP 61

产品细节



## Measuring range - Distance

100 m

## Process temperature

-40 ... 80 °C

## Process pressure

-1 ... 4 bar

## Version

hygienically encapsulated horn antenna  
for separate horn antenna  
with horn antenna  $\varnothing$  40 mm  
with horn antenna  $\varnothing$  48 mm  
with horn antenna  $\varnothing$  75 mm  
with horn antenna  $\varnothing$  95 mm  
with plastic horn antenna  $\varnothing$  80 mm  
Horn antenna  $\varnothing$  1½"  
with encapsulated horn antenna

## Materials, wetted parts

PTFE  
316L  
1.4848  
PP

## Threaded connection

 $\geq$  G1½,  $\geq$  1½ NPT

## Flange connection

 $\geq$  DN50,  $\geq$  2"

## Hygienic fittings

Slotted nut  $\geq$  2", DN50 - DIN 11851  
Varivent  $\geq$  DN25  
DRD connection  $\varnothing$  65 mm  
for NEUMO BioControl D50 PN16 / 316L

## Seal material

FKM  
FFKM

## Housing material

Plastic  
Aluminium  
Stainless steel (precision casting)  
Stainless steel (electropolished)

PRO

## VEGABAR 82

产品细节



## Measuring range - Distance

-

## Measuring range - Pressure

-1 ... 100 bar

## Process temperature

-40 ... 150 °C

## Process pressure

-1 ... 100 bar

## Accuracy

0.05 %

## Materials, wetted parts

PVDF  
316L  
Alloy C22 (2.4602)  
PP  
1.4057  
1.4410  
Alloy C276 (2.4819)  
Duplex (1.4462)  
Titanium Grade 2 (3.7035)

## Threaded connection

 $\geq$  G¼,  $\geq$  ¼ NPT

## Flange connection

 $\geq$  DN15,  $\geq$  ½"

## Hygienic fittings

Clamp  $\geq$  1" - DIN32676, ISO2852  
Slotted nut  $\geq$  DN25 - DIN 11851  
hygienic fitting with tension flange DN32  
hygienic fitting F40 with compression nut  
DRD connection  $\varnothing$  65 mm  
SMS 1145 DN51  
SMS DN38  
Swagelok VCR screwing  
Varivent G125  
Varivent N50-40  
for NEUMO BioControl D50 PN16 / 316L

## Seal material

EPDM  
FKM  
FFKM