



Reliable

Reliable volume measurement of very lightweight media

Cost effective

Optimal use of storage capacity

User friendly

Maintenance-free operation

Styrofoam silo

Level measurement and point level detection in Styrofoam silos

In the manufacture of stucco with special insulating properties, Styrofoam is also added to the traditional sand, lime and cement mixture. With a bulk density of only a few grams per litre, Styrofoam balls are extremely light and therefore very difficult to measure. For cost-effective storage, reliable level measurement and point level detection are required.

[More details](#)



VEGAPULS 6X

Non-contact level measurement with radar in Styrofoam silos

- Easy alignment of measuring instrument thanks to integrated swivel mount and app for smartphones
- Reliable measurement in spite of very lightweight medium
- Maintenance-free operation through use of encapsulated antenna system

[Show Product](#)



VEGAWAVE 62

Overfill protection with vibrating level switch in Styrofoam silos

- Reliable function ensured by product-independent switching point
- High sensitivity even with low bulk densities
- Simple setup without calibration

[Show Product](#)

PRO

VEGAPULS 6X
[Show Product](#)

Measuring range - Distance
 120 m

Process temperature
 -196 ... 450 °C

Process pressure
 -1 ... 160 bar

Accuracy
 ± 1 mm

Frequency
 6 GHz
 26 GHz
 80 GHz

Beam angle
 ≥ 3°

Materials, wetted parts
 PTFE
 PVDF
 316L
 PP
 PEEK

Threaded connection
 ≥ G¾, ≥ ¾ NPT

Flange connection
 ≥ DN20, ≥ ¾"

Hygienic fittings
 Clamp ≥ 1½" - DIN32676, ISO2852
 Slotted nut ≥ 2", DN50 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 Hygienic screw connections ≥ DN50 tube ø53 -
 DIN11864-1-A
 Hygienic flange connection ≥ DN50 DIN11864-2
 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-
 3-A
 DRD connection ø 65 mm
 SMS 1145 DN51

PRO

VEGAWAVE 62
[Show Product](#)

Measuring range - Distance
 -

Process temperature
 -40 ... 150 °C

Process pressure
 -1 ... 6 bar

Version
 Detection of solids in water
 Suspension cable

Materials, wetted parts
 316L
 FEP
 PUR

Threaded connection
 ≥ G1½, ≥ 1½ NPT

Flange connection
 ≥ DN50, ≥ 2"

Seal material
 CR, CSM

Housing material
 Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

Protection rating
 IP66/IP68 (0,2 bar)
 IP66/IP67
 IP66/IP68 (1 bar)